



(1.200-1.400) GHz L-Band Omni Antenna

P/N: 2.5R-1.2-1.4P-XSM-4

Other Frequencies, Connector and Color Options are Available



ISO 9001:2008/FAA Approved Facility

Antenna Mounts/Adapters: <http://www.antcom.com/documents/catalogs/PeripheralAntennaProducts2.pdf>

ANTCOM CORPORATION . 367 Van Ness Way, Suite 602 . Torrance, CA 90501, USA . Tel: (310) 782-1076 . Fax: (310) 782-1086 . E-mail: antennas@antcom.com . <http://www.antcom.com>

NOTICE OF PROPRIETARY RIGHTS		SPECIFICATIONS		REVISIONS																																																																																																					
THIS DOCUMENT CONTAINS CONFIDENTIAL TECHNICAL DATA INCLUDING TRADE SECRETS PROPRIETARY TO ANTCOM CORP. DISCLOSURE OF THIS DATA TO YOU IS EXPRESSLY CONDITIONED UPON YOUR ASSENT THAT ITS USE IS LIMITED TO USE WITHIN YOUR COMPANY ONLY (AND DOES NOT INCLUDE MANUFACTURE OR PROCESSING USES). ANY OTHER USE IS STRICTLY PROHIBITED WITHOUT PRIOR WRITTEN CONSENT OF ANTCOM CORP.				ZONE	REV																																																																																																				
				DESCRIPTION	DATE																																																																																																				
				APPROVED																																																																																																					
		<p>ELECTRICAL:</p> <table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th colspan="2" style="text-align: center;">L-BAND</th> </tr> </thead> <tbody> <tr> <td>FREQUENCY (MHz):</td> <td>(1200-1400)</td> </tr> <tr> <td>PATTERN:</td> <td>OMNIDIRECTIONAL</td> </tr> <tr> <td>POLARIZATION:</td> <td>VERTICAL</td> </tr> <tr> <td>ANTENNA GAIN:</td> <td>> 1 dB</td> </tr> <tr> <td>VSWR:</td> <td>2.1:1</td> </tr> <tr> <td>OUTPUT IMPEDANCE:</td> <td>50 Ω</td> </tr> <tr> <td>POWER HANDLING:</td> <td>100 watts (Without LNA)</td> </tr> <tr> <td>LNA OPTION:</td> <td>GAIN: 20 dB, NF: 4.1 dB, OP1dB: +18dB, OIP3: +33dB DC: (5 to 24) Volt @ <70mA</td> </tr> </tbody> </table> <p>MECHANICAL:</p> <p>SIZE: DIAMETER = 1.000 in. [25.40 mm] HEIGHT = 2.500 in. [63.50 mm]</p> <p>WEIGHT: 1.38 oz. (39 g)</p> <p>FINISH: SKYDROL RESISTANT POLYURETHANE ENAMEL BASE IRIDITE PER MIL-C-5441F</p> <p>MATERIAL: 6061-T6 ALUMINUM ALLOY BASE THERMOSET PLASTIC RADOME, UV, ABRASION AND SKYDROL RESISTANCE</p> <p>CONNECTOR: SMA MALE CONNECTOR (OPTION: (TNC, TNC-BLK, N OR CABLE))</p> <p>ENVIRONMENTAL:</p> <p>TEMPERATURE: -67°F TO +185°F [-55°C TO +85°C]</p> <p>ALTITUDE: 70,000 ft.</p> <p>VIBRATION: >10 G's</p> <p>LEAKAGE: HERMETICALLY SEALED</p> <p>FEDERAL & MILITARY SPECIFICATIONS:</p> <p>DESIGN TO: DO-160D, MIL-C-5541, MIL-E-5400, MIL-I-45208A, AND MIL-STD-810E</p>	L-BAND		FREQUENCY (MHz):	(1200-1400)	PATTERN:	OMNIDIRECTIONAL	POLARIZATION:	VERTICAL	ANTENNA GAIN:	> 1 dB	VSWR:	2.1:1	OUTPUT IMPEDANCE:	50 Ω	POWER HANDLING:	100 watts (Without LNA)	LNA OPTION:	GAIN: 20 dB, NF: 4.1 dB, OP1dB: +18dB, OIP3: +33dB DC: (5 to 24) Volt @ <70mA	<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th>1</th> <th>DESCRIPTION</th> <th>PART NO</th> <th>SPECIFICATION</th> <th>MATERIAL</th> <th>FINISH</th> <th>ITEM No</th> </tr> </thead> <tbody> <tr> <td style="text-align: center;">1</td> <td>UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES</td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td>FRACTIONS DECIMALS ANGLES</td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td>± 1/64 ±.005 ± .1°</td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td>TOLERANCE SYM PER ANSI Y14.5</td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td>REMOVE ALL BURRS</td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td>BREAK EXTERNAL EDGES .005 TO .016</td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td>FILLETS R .005 TO R .030</td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td>SCREW THREADS PER MIL-S-8879</td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td>DIA'S ON A COMMON 6</td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td>MACHINED SURFACES 125</td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td>DO NOT SCALE DRAWING</td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> </tbody> </table>	1	DESCRIPTION	PART NO	SPECIFICATION	MATERIAL	FINISH	ITEM No	1	UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES							FRACTIONS DECIMALS ANGLES							± 1/64 ±.005 ± .1°							TOLERANCE SYM PER ANSI Y14.5							REMOVE ALL BURRS							BREAK EXTERNAL EDGES .005 TO .016							FILLETS R .005 TO R .030							SCREW THREADS PER MIL-S-8879							DIA'S ON A COMMON 6							MACHINED SURFACES 125							DO NOT SCALE DRAWING					
L-BAND																																																																																																									
FREQUENCY (MHz):	(1200-1400)																																																																																																								
PATTERN:	OMNIDIRECTIONAL																																																																																																								
POLARIZATION:	VERTICAL																																																																																																								
ANTENNA GAIN:	> 1 dB																																																																																																								
VSWR:	2.1:1																																																																																																								
OUTPUT IMPEDANCE:	50 Ω																																																																																																								
POWER HANDLING:	100 watts (Without LNA)																																																																																																								
LNA OPTION:	GAIN: 20 dB, NF: 4.1 dB, OP1dB: +18dB, OIP3: +33dB DC: (5 to 24) Volt @ <70mA																																																																																																								
1	DESCRIPTION	PART NO	SPECIFICATION	MATERIAL	FINISH	ITEM No																																																																																																			
1	UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES																																																																																																								
	FRACTIONS DECIMALS ANGLES																																																																																																								
	± 1/64 ±.005 ± .1°																																																																																																								
	TOLERANCE SYM PER ANSI Y14.5																																																																																																								
	REMOVE ALL BURRS																																																																																																								
	BREAK EXTERNAL EDGES .005 TO .016																																																																																																								
	FILLETS R .005 TO R .030																																																																																																								
	SCREW THREADS PER MIL-S-8879																																																																																																								
	DIA'S ON A COMMON 6																																																																																																								
	MACHINED SURFACES 125																																																																																																								
	DO NOT SCALE DRAWING																																																																																																								
<p>P/N: 2.5R-1.2-1.4P-XSM-4</p>		<p>ANTCOM CORP. TORRANCE CALIFORNIA</p> <p>L-Band Omni Antenna</p>		SIZE	CASE NO	DRAWING NO	REV																																																																																																		
				D	3CVE1	2.5R-1.2-1.4P-XSM-4	-																																																																																																		
				SCALE 1/1		SHEET 1 OF 1																																																																																																			