




IRIDIUM/GPS Antenna, P/N: 0.5R1216P-XTM-4

0.5" Diameter x 4.4" Tall, Threaded Bottom Mount Configuration



ISO 9001:2008/FAA Approved Facility Antenna Mounts: <http://www.antcom.com/documents/catalogs/PeripheralAntennaProducts2.pdf>

ANTCOM CORPORATION . 367 Van Ness Way, Suite 602 . Torrance, CA 90501 . Tel: (310) 782-1076 . Fax: (310) 782-1086 . E-mail: antennas@antcom.com . <http://www.antcom.com>

NOTICE OF PROPRIETARY RIGHTS
THIS DOCUMENT CONTAINS CONFIDENTIAL, TECHNICAL DATA INCLUDING TRADE SECRETS PROPRIETARY TO ANTCOM CORP. DISCLOSURE OF THIS DATA TO YOU IS EXPRESSLY PROHIBITED UNLESS YOU AGREE THAT ITS USE IS LIMITED TO USE WITH YOUR COMPANY ONLY AND DOES NOT INCLUDE REPRODUCTION OR MODIFICATION. ANY OTHER USE IS EXPRESSLY PROHIBITED WITHOUT PRIOR WRITTEN CONSENT OF ANTCOM CORP.

SPECIFICATIONS

ELECTRICAL:

FREQUENCY (MHz):	(1575.42 ±15)	(1542.50 ±17.5)	(1642.50 ±17.5)	(1602-1616)	(1610-1626)
GAIN in FS/3in GP (dBic)	L1 GPS	Rx INMARSAT	Tx INMARSAT	GLONASS	IRIDIUM
@ 90° (Zenith):	-1.6	-2.9	+0.1	+0.5	+0.5
@ 10° Elevation:	-4.5	-6.0	-2.1	-2.0	-2.0
@ 20° Elevation:	-3.5	-5.0	-1.1	-0.9	-0.9
@ 30° Elevation:	-2.8	-4.2	-0.7	-0.3	-0.3
@ 45° Elevation:	-2.3	-3.5	-0.2	+0.3	+0.3
@ 70° Elevation:	-1.8	-3.0	-0.4	+0.2	+0.2
BEAM WIDTH (3dB)	152 Deg.	150 Deg.	170 Deg.	1 to 3	160 Deg.
AXIAL RATIO (dB)	1 to 3	1 to 3	1 to 3	1 to 3	1 to 3
RADIATION PATTERN:	HEMISPHERICAL				
POLARIZATION:	RHCP				
VSWR:	< 2.0:1				

LNA OPTION for GPS:

LNA GAIN: (27.0+/-2.0) dB
LNA NOISE FIGURE: <1.4 dB
LNA P 1dB Out: +13 dBm
VOLTAGE/CURRENT: (3-10) Volts/ 20mA

MECHANICAL:

SIZE: DIAMETER: 0.50 in. [12.70 mm]
HEIGHT: 5.517 in. [140 mm]
WEIGHT: 0.92 oz (26 g)
FINISH: SKYDROL RESISTANT POLYURETHANE ENAMEL, BLACK ANODIZING (MIL-A-8625F, Type II Class II)
COLOR: See Below Description
MATERIAL: 6061-T6 ALUMINUM ALLOY BASE COMPOSITE RADOME, IMPACT, ABRASION, UV, SOLVENT, SKYDROL RESISTANCE, AND FIRE RETARDANT
CONNECTOR: TNC MALE (OPTION: MMCX, MCX, SMP, SSMC, SMA, BNC TNC FEMALE, TNC-BULKHEAD, N, N-BULKHEAD, or Cable)

ENVIRONMENTAL:

TEMPERATURE: -67 °F TO +185 °F [-55 °C TO +85 °C]
ALTITUDE: 70,000 ft.
VIBRATION: > 30 G's
LEAKAGE: HERMETICALLY SEALED

FEDERAL & MILITARY SPECIFICATIONS:

DESIGN TO: FAA TSO-C144, DO-160D, D0-228, MIL-A-8625F, MIL-E-5400, MIL-I-45208A, MIL-STD-810, AND SAE J1455

ACCEPTANCE TEST PROCEDURE: ATP-GPS-L1L2-100

CONFIGURATION:	FREQUENCY:	LNA:	CABLE'S LENGTH:	FEMALE CONNECTOR:	COLOR:
1: 2" SQ. (FLAT)	1216: L1/L2/Inmarsat	A1: WITH LNA	X: NO CABLE	S: SMA; P: PINS	-1: GLOSS WHITE #17925 PER FED-STD-595B
1.9: 1.9" SQ. (FLAT)	1215: L1/L2	M: WITHOUT LNA	M: WITH MAG. MOUNT	M: MCX; MM: MMCX	-2: LUSTERLESS GRAY #38320 PER FED-STD-595B
2: 2.8" DIA. (FLAT)	15: L1	R: TNC FEMALE	#: CABLE LENGTH (IN)	SMP; SSMC; B: BNC	-3: OLIVE DRAB GREEN #34031 PER FED-STD-595B
3: 3.5" DIA. (FLAT)	RR: TX: RHCP, RX: RHCP	T: TNC MALE	R: RIGHT ANGLE CON.	T: TNC; TB: TNC-Bulkhead	-4: Natural Back Color from Ultem 2200 Black (20% Glass)
0.5R: 0.5" DIA. RHCP-HELIX					-5: Desert Tan
0.5T: 0.5" DIA. LHCP-HELIX					
53: (HELIX ROD)					
5B: (HELIX BLADE)					
3D: (HELIX HANDHELD)					

P/N: 0.5R1216P-XTM-4

NOTES: UNLESS OTHERWISE SPECIFIED:
1. DIMENSIONS IN BRACKETS ARE IN MILLIMETERS [mm]
2. ALL SCREWS ARE SUPPLIED BY ANTCOM CORPORATION

NMO Connector Option is Now Available for Some Antennas