




Active L1/L2 GPS Antenna, P/N: 1.2G1215A4-12NRMM-4 Rev B

(Improved Gain) 1.2" Square, Flat Mount Configuration

with 12in Right Angle MMCX Male Cable



ISO 9001:2008/FAA Approved Facility

Antenna Mounts: <http://www.antcom.com/documents/catalogs/PeripheralAntennaProducts2.pdf>

ANTCOM CORPORATION . 367 Van Ness Way, #602 . Torrance, CA 90501 . Tel: (310) 782-1076 . Fax: (310) 782-1086 . E-mail: antennas@antcom.com . <http://www.antcom.com>

NOTICE OF PROPRIETARY RIGHTS

THIS DOCUMENT CONTAINS CONFIDENTIAL, TECHNICAL DATA INCLUDING TRADE SECRETS PROPRIETARY TO ANTCOM CORP. REUSE OF THIS DATA BY YOU IS EXPRESSLY FORBIDDEN UNLESS YOU AGREE THAT ITS USE IS LIMITED TO USE WITHIN YOUR COMPANY ONLY AND DOES NOT INCLUDE REPRODUCTION OR REVERSE ENGINEERING. ANY OTHER USE IS EXPRESSLY FORBIDDEN WITHOUT PRIOR WRITTEN CONSENT OF ANTCOM CORP.

SPECIFICATIONS

ELECTRICAL:

	L1: (1575.42 ±12) MHz	L2: (1227.60 ±12) MHz
FREQUENCY:		
RADIATION PATTERN:	HEMISPHERICAL	
POLARIZATION:	RHCP	
VSWR:	< 1.5:1	< 1.5:1
IMPEDANCE:	50 ohms	50 ohms
ANTENNA GAIN (dBic):	Free Space 3 in G.P.	Free Space 3 in G.P.
@ 90° (ZENITH):	-0.8 +3.8	-3.7 +2.7
@ 10° Elevation:	-9.3 -4.3	-9.9 -6.3
@ 20° Elevation:	-6.8 -2.2	-9.2 -4.2
@ 30° Elevation:	-5.2 -0.7	-7.8 -2.4
@ 60-90° Elevation:	> -2.1 > 2.5	> -4.7 > 1.3
BEAM WIDTH (3dB):	100 Deg. 120 Deg.	100 Deg. 90 Deg.
AXIAL RATIO:	2.5 dB 3	
LIGHTNING PROTECTION:	DC GROUNDING	

LNA OPTION:

LNA GAIN: 24.0 dB
 LNA NOISE FIGURE: 1.8 dB
 LNA P 1dB Out: +16 dBm
 VOLTAGE/CURRENT: (+2.8 TO +28) Volts DC / (15 TO 25) mA

MECHANICAL:

SIZE: 1.250 in. [31.75 mm] SQ.
 HEIGHT: 0.547 in. [13.89 mm]
 WEIGHT: 1.1 oz. (31.2 g)
 FINISH: SKYDROL RESISTANT POLYURETHANE ENAMEL BASE IRIDITE PER MIL-C-5441
 MATERIAL: 6061-T6 ALUMINUM ALLOY BASE COMPOSITE RADOME, ABRASION, UV, SOLVENT, SKYDROL RESISTANCE, AND FIRE RETARDANT
 CONNECTOR: 4.5" LONG FLEXIBLE CABLE WITH RIGHT ANGLE MMCX (OPTION: MCX, SMA, SMB, SSMA, SSMB, SSMC, OR TNC)

ENVIRONMENTAL:

TEMPERATURE: -67 °F TO +185 °F [-55 °C TO +85 °C]
 ALTITUDE: 70,000 ft.
 VIBRATION: > 30 G's
 LEAKAGE: HERMETICALLY SEAL

FEDERAL & MILITARY SPECIFICATIONS:

DESIGN TO: FAA TSO-C144, DO-160D, D0-228, MIL-C-5541, MIL-E-5400, MIL-I-45208A, MIL-STD-810, AND SAE J1455

ACCEPTANCE TEST PROCEDURE: ATP-GPS-L1L2-100

1. DIMENSIONS IN BRACKETS ARE IN MILLIMETERS [mm]

NOTES: UNLESS OTHERWISE SPECIFIED:

SIZE	FREQ. BAND	LNA:
1: 1.2" SQ.	1215: L1/L2	A2: WITH 20 dB LNA
1.8: 1.8" SQ.	15: L1 ONLY	A4: WITH 40 dB LNA
2: 2.6" DIA.		P: WITHOUT LNA
3: 3.5" DIA.		
4: MINIARINC		

P/N: 1.2G1215A2-XNMM-4

CABLE LENGTH	CONNECTOR	COLOR
X: NO CABLE	S: SMA; RS: R-SMA; P: PINS; M: MCX	-1: GLOSS WHITE #H7925PER FED-STD-595B
M: MAG. N. NO MAG.	MM: MMCX; SMB: SSMA; SSMB: SSMC	-2: LUSTERLESS GRAY #3820PER FED-STD-595B
R: CABLE LENGTH (IN)	SSMP: T; TB: TNC; TNC-Bulkhead	-3: OLIVEDRAB GREEN #34031PER FED-STD-595B
R: RIGHT ANGLE CON.	L-RM: Right Angle Male Lemo	-4: LUSTERLESS BLACK #37038PER FED-STD-595B

QUANTITY REQD	DESCRIPTION	PART NO	SPECIFICATION	MATERIAL	FINISH	ITEM NO.
1	ADHESIVE GASKET	12345G-3M-1.2G				5
1						3
1						2
1						1
-2	-1					

UNLESS OTHERWISE SPECIFIED TOLERANCES ARE IN INCHES

FRACTIONS	DECIMALS	ANGLES
± 1/64	± .005	± 1°

TOLERANCE .5M PER ANS Y14.3

REMOVE ALL BURRS

BREAK CRITICAL EDGES .005 TO .015

FILLET R .005 TO R .030

SPRUE FINISHES PER MIL-C-20000

MACHINED SURFACES

DO NOT SCALE DRAWING

ANTCOM CORP. TORRANCE, CALIFORNIA

OUTLINE DRAWING

L1/L2 ACTIVE OR PASSIVE

GPS ANTENNA

APPROVED: S. HUYNH Mar-11-05

DATE: 03/04/05

SCALE: 1/1

SHEET 1 OF 1

NMO Connector Option is Now Available for Some Antennas