



FAA Approved Facility

RHCP/LHCP L1/L2 GPS Antenna, P/N: 1.9G1215P2-20SSMC-3
Dual Linear (V/H) L1/L2 GPS Antenna, P/N: 1.9G1215P2L-20SSMC-3
Low Profile 1.9" Square, Flat/Back Mount Epoxy On Configuration
Suitable for Forming Multiple Element CRPA

Antenna Mounts: <http://www.antcom.com/documents/catalogs/PeripheralAntennaProducts2.pdf>



ANTCOM CORPORATION . 367 Van Ness Way, Suite 602 . Torrance, CA 90501 . Tel: (310) 782-1076 . Fax: (310) 782-1086 . E-mail: antennas@antcom.com . <http://www.antcom.com>

NOTICE OF PROPRIETARY RIGHTS		SPECIFICATION S		REVISIONS																																																																																										
THIS DOCUMENT CONTAINS CONFIDENTIAL TECHNICAL DATA INCLUDING TRADE SECRETS PROPRIETARY TO ANTCOM CORP. DISCLOSURE OF THIS DATA TO YOU IS EXPRESSLY CONDITIONED UPON YOUR AGREEMENT THAT ITS USE IS LIMITED TO USE WITHIN YOUR COMPANY ONLY (AND DOES NOT INCLUDE MANUFACTURE OR PROCESSING USES). ANY OTHER USE IS STRICTLY PROHIBITED WITHOUT PRIOR WRITTEN CONSENT OF ANTCOM CORP.				ZONE	REV	DESCRIPTION	DATE	APPROVED																																																																																						
		ELECTRICAL:																																																																																												
		<table border="1" style="width:100%; border-collapse: collapse; font-size: 8px;"> <tr> <td>FREQUENCY:</td> <td colspan="2">L1: (1575.42±12) MHz</td> <td colspan="3">L2: (1227.60±12) MHz</td> </tr> <tr> <td>RADIATION PATTERN:</td> <td colspan="5">HEMISPHERICAL</td> </tr> <tr> <td>POLARIZATION:</td> <td colspan="5">RHCP/LHCP</td> </tr> <tr> <td>VSWR:</td> <td colspan="2">< 1.5:1</td> <td colspan="3">< 1.5:1</td> </tr> <tr> <td>IMPEDANCE:</td> <td colspan="2">50 ohms</td> <td colspan="3">50 ohms</td> </tr> <tr> <td>ANTENNA GAIN (dBi):</td> <td>Free Space</td> <td>3 in G.P.</td> <td>4 ft G.P.</td> <td>Free Space</td> <td>3 in G.P.</td> <td>4 ft G.P.</td> </tr> <tr> <td>@ 90 ° (ZENITH):</td> <td>+ 2.7</td> <td>+ 4.7</td> <td>+ 3.1</td> <td>+ 1.5</td> <td>+ 3.3</td> <td>+ 4.5</td> </tr> <tr> <td>@ 10 ° Elevation:</td> <td>- 4.4</td> <td>- 1.8</td> <td>- 1.9</td> <td>- 6.7</td> <td>- 3.8</td> <td>- 3.5</td> </tr> <tr> <td>@ 20 ° Elevation:</td> <td>- 2.3</td> <td>- 0.3</td> <td>+ 0.6</td> <td>- 5.6</td> <td>- 2.0</td> <td>- 0.8</td> </tr> <tr> <td>@ 30 ° Elevation:</td> <td>- 0.8</td> <td>+ 1.4</td> <td>+ 1.7</td> <td>- 4.5</td> <td>- 0.5</td> <td>+ 1.4</td> </tr> <tr> <td>@ 60 - 90 ° Elevation:</td> <td>> 2.0</td> <td>> 3.9</td> <td>> 2.4</td> <td>> 0.0</td> <td>> 2.7</td> <td>> 2.2</td> </tr> <tr> <td>BEAM WIDTH (3dB):</td> <td>113 Deg.</td> <td>114 Deg.</td> <td>143 Deg.</td> <td>85 Deg.</td> <td>106 Deg.</td> <td>74 Deg.</td> </tr> <tr> <td>AXIAL RATIO:</td> <td colspan="5">2 dB</td> </tr> <tr> <td>LIGHTNING PROTECTION:</td> <td colspan="5">DC GROUNDING</td> </tr> </table>		FREQUENCY:	L1: (1575.42±12) MHz		L2: (1227.60±12) MHz			RADIATION PATTERN:	HEMISPHERICAL					POLARIZATION:	RHCP/LHCP					VSWR:	< 1.5:1		< 1.5:1			IMPEDANCE:	50 ohms		50 ohms			ANTENNA GAIN (dBi):	Free Space	3 in G.P.	4 ft G.P.	Free Space	3 in G.P.	4 ft G.P.	@ 90 ° (ZENITH):	+ 2.7	+ 4.7	+ 3.1	+ 1.5	+ 3.3	+ 4.5	@ 10 ° Elevation:	- 4.4	- 1.8	- 1.9	- 6.7	- 3.8	- 3.5	@ 20 ° Elevation:	- 2.3	- 0.3	+ 0.6	- 5.6	- 2.0	- 0.8	@ 30 ° Elevation:	- 0.8	+ 1.4	+ 1.7	- 4.5	- 0.5	+ 1.4	@ 60 - 90 ° Elevation:	> 2.0	> 3.9	> 2.4	> 0.0	> 2.7	> 2.2	BEAM WIDTH (3dB):	113 Deg.	114 Deg.	143 Deg.	85 Deg.	106 Deg.	74 Deg.	AXIAL RATIO:	2 dB					LIGHTNING PROTECTION:	DC GROUNDING				
FREQUENCY:	L1: (1575.42±12) MHz		L2: (1227.60±12) MHz																																																																																											
RADIATION PATTERN:	HEMISPHERICAL																																																																																													
POLARIZATION:	RHCP/LHCP																																																																																													
VSWR:	< 1.5:1		< 1.5:1																																																																																											
IMPEDANCE:	50 ohms		50 ohms																																																																																											
ANTENNA GAIN (dBi):	Free Space	3 in G.P.	4 ft G.P.	Free Space	3 in G.P.	4 ft G.P.																																																																																								
@ 90 ° (ZENITH):	+ 2.7	+ 4.7	+ 3.1	+ 1.5	+ 3.3	+ 4.5																																																																																								
@ 10 ° Elevation:	- 4.4	- 1.8	- 1.9	- 6.7	- 3.8	- 3.5																																																																																								
@ 20 ° Elevation:	- 2.3	- 0.3	+ 0.6	- 5.6	- 2.0	- 0.8																																																																																								
@ 30 ° Elevation:	- 0.8	+ 1.4	+ 1.7	- 4.5	- 0.5	+ 1.4																																																																																								
@ 60 - 90 ° Elevation:	> 2.0	> 3.9	> 2.4	> 0.0	> 2.7	> 2.2																																																																																								
BEAM WIDTH (3dB):	113 Deg.	114 Deg.	143 Deg.	85 Deg.	106 Deg.	74 Deg.																																																																																								
AXIAL RATIO:	2 dB																																																																																													
LIGHTNING PROTECTION:	DC GROUNDING																																																																																													
		MECHANICAL:																																																																																												
		SIZE:		1.912 in.[48.56mm] SQ.																																																																																										
		WEIGHT:		2.4 oz. (68 g)																																																																																										
		FINISH:		SKYDROLRESISTANTPOLYURETHANENAMEL BASE IRIDITE PER MIL-C-5441																																																																																										
		MATERIAL:		6061-T6ALUMINUMALLOY BASE THERMOSETPLASTICRADOME,UV, ABRASIONAND SKYDROL RESISTANCE																																																																																										
		CONNECTOR:		20 IN SSMCMALE CABLES (OPTION: SMC, SMB, SSB, SMA, PIN, TNC, TNC-Bulkhead, N, N-Bulkhead, MCX, MMCX, or Cable)																																																																																										
		ENVIRONMENTAL:																																																																																												
		TEMPERATURE:		-67 °F TO +185 °F [-55 °C TO +85 °C]																																																																																										
		ALTITUDE:		70,000ft.																																																																																										
		VIBRATION:		>30 G's																																																																																										
		LEAKAGE:		HERMETICALLYSEAL																																																																																										
		FEDERAL & MILITARY SPECIFICATIONS																																																																																												
		DESIGN TO:		FAA TSO-C144, DO-160D, DO-228, MIL-C-5541, MIL-E-5400, MIL-I-45208A, AND MIL-STD-810																																																																																										
				<table border="1" style="width:100%; border-collapse: collapse; font-size: 8px;"> <tr> <td>1</td> <td>ADHESIVE GASKET</td> <td>12345G-3M-1G</td> <td>-</td> <td>-</td> <td>-</td> <td>1</td> </tr> <tr> <td></td> <td>DESCRIPTION</td> <td>PART NO</td> <td>SPECIFICATION</td> <td>MATERIAL</td> <td>FINISH</td> <td>ITEM NO</td> </tr> </table>				1	ADHESIVE GASKET	12345G-3M-1G	-	-	-	1		DESCRIPTION	PART NO	SPECIFICATION	MATERIAL	FINISH	ITEM NO																																																																									
1	ADHESIVE GASKET	12345G-3M-1G	-	-	-	1																																																																																								
	DESCRIPTION	PART NO	SPECIFICATION	MATERIAL	FINISH	ITEM NO																																																																																								
				<table border="1" style="width:100%; border-collapse: collapse; font-size: 8px;"> <tr> <td colspan="2">UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES</td> <td colspan="2" rowspan="2" style="text-align: center;">ANTCOM CORP. TORRANCE CALIFORNIA</td> </tr> <tr> <td>FRACTIONS</td> <td>DECIMALS</td> </tr> <tr> <td>± 1/64</td> <td>.XXX, .020 XXXX, .010</td> <td>± 1°</td> <td></td> </tr> <tr> <td colspan="2">TOLERANCE SYM PER ANS Y14.5</td> <td>CHECKED</td> <td></td> </tr> <tr> <td colspan="2">REMOVE ALL BURRS</td> <td>ENGINEER</td> <td></td> </tr> <tr> <td colspan="2">BREAK EXTERNAL EDGES .005 TO .015</td> <td>APPROVED</td> <td></td> </tr> <tr> <td colspan="2">FILLETS R .005 TO R .030</td> <td>S. HUYNH</td> <td></td> </tr> <tr> <td colspan="2">SCREW THREADS PER MIL-C-8879</td> <td>Sep-19-01</td> <td></td> </tr> <tr> <td colspan="2">DIAS ON A COMMON & 2X.005</td> <td>CAP FILE NO</td> <td></td> </tr> <tr> <td colspan="2">MACHINED SURFACES 15/</td> <td>DO NOT SCALE DRAWING</td> <td></td> </tr> </table>				UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES		ANTCOM CORP. TORRANCE CALIFORNIA		FRACTIONS	DECIMALS	± 1/64	.XXX, .020 XXXX, .010	± 1°		TOLERANCE SYM PER ANS Y14.5		CHECKED		REMOVE ALL BURRS		ENGINEER		BREAK EXTERNAL EDGES .005 TO .015		APPROVED		FILLETS R .005 TO R .030		S. HUYNH		SCREW THREADS PER MIL-C-8879		Sep-19-01		DIAS ON A COMMON & 2X.005		CAP FILE NO		MACHINED SURFACES 15/		DO NOT SCALE DRAWING																																																		
UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES		ANTCOM CORP. TORRANCE CALIFORNIA																																																																																												
FRACTIONS	DECIMALS																																																																																													
± 1/64	.XXX, .020 XXXX, .010	± 1°																																																																																												
TOLERANCE SYM PER ANS Y14.5		CHECKED																																																																																												
REMOVE ALL BURRS		ENGINEER																																																																																												
BREAK EXTERNAL EDGES .005 TO .015		APPROVED																																																																																												
FILLETS R .005 TO R .030		S. HUYNH																																																																																												
SCREW THREADS PER MIL-C-8879		Sep-19-01																																																																																												
DIAS ON A COMMON & 2X.005		CAP FILE NO																																																																																												
MACHINED SURFACES 15/		DO NOT SCALE DRAWING																																																																																												
				<table border="1" style="width:100%; border-collapse: collapse; font-size: 8px;"> <tr> <td>SIZE</td> <td>CASE NO</td> <td>DRAWING NO</td> <td>REV</td> </tr> <tr> <td>D 3CVE1</td> <td>1.9G1215P2-20SSMC-3</td> <td></td> <td></td> </tr> <tr> <td>SCALE 1/1</td> <td colspan="2">SHEET 1 OF 1</td> <td></td> </tr> </table>				SIZE	CASE NO	DRAWING NO	REV	D 3CVE1	1.9G1215P2-20SSMC-3			SCALE 1/1	SHEET 1 OF 1																																																																													
SIZE	CASE NO	DRAWING NO	REV																																																																																											
D 3CVE1	1.9G1215P2-20SSMC-3																																																																																													
SCALE 1/1	SHEET 1 OF 1																																																																																													
				<table border="1" style="width:100%; border-collapse: collapse; font-size: 8px;"> <tr> <td>CABLES LENGTH:</td> <td>CONNECTOR:</td> <td>COLOR:</td> </tr> <tr> <td>X: NO CABLE</td> <td>S: SMA, P: P2: PINS</td> <td>1: GLOSS WHITE #17925 PER FED-STD-595B</td> </tr> <tr> <td>M: MAG, N: NO MAG</td> <td>M: MCX, MM: MMCX</td> <td>2: LUSTERLESS GRAY #36320 PER FED-STD-595B</td> </tr> <tr> <td>F: CABLE LENGTH (IN)</td> <td>N, NB: RS, R: SMA</td> <td>3: OLIVE DRAB GREEN #34031 PER FED-STD-595B</td> </tr> <tr> <td>R: RIGHT ANGLE CON:</td> <td>T, TB: TNC, TNC-Bulkhead</td> <td>4: LUSTERLESS BLACK #37038 PER FED-STD-595B</td> </tr> </table>				CABLES LENGTH:	CONNECTOR:	COLOR:	X: NO CABLE	S: SMA, P: P2: PINS	1: GLOSS WHITE #17925 PER FED-STD-595B	M: MAG, N: NO MAG	M: MCX, MM: MMCX	2: LUSTERLESS GRAY #36320 PER FED-STD-595B	F: CABLE LENGTH (IN)	N, NB: RS, R: SMA	3: OLIVE DRAB GREEN #34031 PER FED-STD-595B	R: RIGHT ANGLE CON:	T, TB: TNC, TNC-Bulkhead	4: LUSTERLESS BLACK #37038 PER FED-STD-595B																																																																								
CABLES LENGTH:	CONNECTOR:	COLOR:																																																																																												
X: NO CABLE	S: SMA, P: P2: PINS	1: GLOSS WHITE #17925 PER FED-STD-595B																																																																																												
M: MAG, N: NO MAG	M: MCX, MM: MMCX	2: LUSTERLESS GRAY #36320 PER FED-STD-595B																																																																																												
F: CABLE LENGTH (IN)	N, NB: RS, R: SMA	3: OLIVE DRAB GREEN #34031 PER FED-STD-595B																																																																																												
R: RIGHT ANGLE CON:	T, TB: TNC, TNC-Bulkhead	4: LUSTERLESS BLACK #37038 PER FED-STD-595B																																																																																												
				<p>1. DIMENSIONS IN BRACKETS ARE IN MILLIMETERS [mm]</p> <p style="font-size: 12px; font-weight: bold;">P/N: 1.9G1215P2-20SSMC-3</p>																																																																																										

http://www.antcom.com/documents/catalogs/PeripheralAntennaProducts1.pdf (Amplifiers/Power Divider/Combiner/Filters)