



(130 – 170)/(400 - 470) MHz Dual VHF/UHF Antenna for Deep Sea Applications

P/N: 152-013017-040047V-XDGO-UU (For DGO Connectors)

P/N: 152-013017-040047V-XX-2-UU (For Other Connectors)

(900-930) MHz, (2.4-2.5) GHz, Other Frequencies and Connectors are Available. *Depth Rate = 10 Km (1455 PSI)*

ISO 9001:2008/FAA Approved Facility Antenna Mounts/Adapters: <http://www.antcom.com/documents/catalogs/PeripheralAntennaProducts2.pdf>



ANTCOM CORPORATION . 367 Van Ness Way, Suite 602 . Torrance, CA 90501, USA . Tel: (310) 782-1076 . Fax: (310) 782-1086 . E-mail: antennas@antcom.com . <http://www.antcom.com>

NOTICE OF PROPRIETARY RIGHTS
THIS DOCUMENT CONTAINS CONFIDENTIAL, TECHNICAL DATA INCLUDING TRADE SECRETS PROPRIETARY TO ANTCOM CORP. DISCLOSURE OF THIS DATA TO YOU IS EXPRESSLY CONDITIONED UPON YOUR AGREEMENT THAT THE USE IS LIMITED TO USE WITHIN YOUR COMPANY ONLY AND DOES NOT INCLUDE REPRODUCTION OR REUSE FOR ANY OTHER USE OR IN ANY MANNER WITHOUT PRIOR WRITTEN CONSENT OF ANTCOM CORP.

DGO CONNECTOR

O-RING
P/N: AS568A-023
O.D.: $\phi 1.278$ [32.46]
I.D.: $\phi 1.090$ [27.69]

4X 10-32 UNC
.700 Deep
On 1.153 RAD.

CLEARANCE DIA. .866

SPECIFICATIONS

ELECTRICAL:

FREQUENCY:	(130 - 170) / (400 - 470) MHz
RADIATION PATTERN:	OMNI
POLARIZATION:	VERTICAL
VSWR:	< 2.0:1
GAIN (dB):	1/4 Wave Monopole
Elevation Beam Width (3dB):	(50 to 70) °
Azimuth Beam Width (3dB):	360 °
IMPEDANCE:	50 Ohms
POWER HANDLING:	200 Watt

MECHANICAL:

SIZE: BASE DIAMETER = 2.692 in. [68.38 mm],
HEIGHT = 15.00 in [381.00mm]

WEIGHT: 1.8 lbs. (816 g)

FINISH: SKYDROL RESISTANT POLYURETHANE ENAMEL
BASE IRIDITE PER MIL-C-5441

MATERIAL: 6061-T6 ALUMINUM ALLOY BASE
COMPOSITE RADOME, IMPACT, ABRASION, UV, SOLVENT,
SKYDROL RESISTANCE, AND FIRE RETARDANT

CONNECTOR: DGO FEMALE
(OPTION: SMA, TNC, N, BNC)

ENVIRONMENTAL:

TEMPERATURE: -67 °F TO +185 °F [-55 °C TO +85 °C]

ALTITUDE: 70,000 ft.

VIBRATION: > 30 G's

LEAKAGE: HERMETICALLY SEAL

FEDERAL & MILITARY SPECIFICATIONS:

DESIGN TO: FAA TSO-C144, DO-160D, D0-228, MIL-C-5541,
MIL-E-5400, MIL-I-45208A, MIL-STD-810, AND SAE J1455

ACCEPTANCE TEST PROCEDURE: ATP-GPS-4.1L2-100

ZONE	REV	DESCRIPTION	DATE	APPROVED
1	0			
2	1			
3	1			

QTY	DESCRIPTION	PART NO	MATERIAL	ITEM NO
1	O-RING	AS568A-023, Item 553-023		2
3	SCREW, 10-32, 1.125"L	91772A834, Item 544-834		1

FREQUENCY (GHz)	POLARIZATION:	CONNECTOR:	COLOR:
013017: (130-170) MHz	V: VERTICAL	S: SMA; P: PINS	-1: GLOSS WHITE #17925 PER FED-STD-595B
0.174-0.180: (174-180) MHz	L: LHCP	N: MCX; MM: MMCX	-2: LUSTERLESS GRAY #36320 PER FED-STD-595B
0.180-0.186: (180-186) MHz	R: RHCP	N: N; NB: N-Bulkhead	-3: OLIVE DRAB GREEN #34031 PER FED-STD-595B
0.186-0.192: (186-192) MHz		T: TNC; TB: TNC-Bulkhead	-4: LUSTERLESS BLACK #37038 PER FED-STD-595B
D40047: (400-470) MHz		DGO: DGO	-5: TAN #33446 PER FED-STD-595B
X:XX-Y:YY;X:XX-Y:YY GHz			UU: Gray Color Teflon Coating

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES TOLERANCES ARE DECIMAL ANGLES ± 1°	ORIGINAL DRAWN	DATE
TOLERANCE SURF PER ANSI Y14.5 REMOVE ALL SHARP BREAK EXTERNAL EDGES .005 TO .015 FILED & .005 TO .010 SCREW THREADS PER MIL-S-8870 DATE ON A COMBINATION OF MACHINED SURFACES	S. HUYNH	Sept-30-14
	S. HUYNH	Sept-30-14
	S. HUYNH	July-28-15
	P. TRAM	July-28-15
	S. HUYNH	July-28-15

ANTCOM CORP. TORRANCE, CALIFORNIA	
(130-170)/(400-470) MHz VHF/UHF OMNI ANTENNA	
REV: D	SCALE: 1/1
DATE: 152-013017-040047V-XDGO-UU	SHEET 1 OF 1

NMO Connector Option is Now Available for Some Antennas

P/N: 152-013017-040047V-XDGO-UU