



New High Gain Array Antenna

P/N: 18X18A-TL-P-XT-1 (Thuraya); P/N: 18X18A-INR-P-XT-1 (Inmarsat/Iridium)
 P/N: 18X18A-1.6-1.9V-P-XT-1 (1.6 - 1.9 GHz); P/N: 18X18A-2.2-2.3V-P-XT-1 (2.2 - 2.3 GHz)
 P/N: 18X18A-2.2-2.4V-P-XT-1 (2.2 - 2.4 GHz); P/N: 18X18A-2.2-2.5V-P-XT-1 (2.2 - 2.5 GHz)
 P/N: 18X18A-2.4-2.5V-P-XT-1 (2.4 - 2.5 GHz); P/N: 18X18A-LSV-P-XT-1 ((1.625 - 1.85)/(2.2 - 2.4) GHz)



ISO 9001:2008/FAA Approved Facility Antenna Mounts/Adapters: <http://www.antcom.com/documents/catalogs/PeripheralAntennaProducts2.pdf>

ANTCOM CORPORATION . 367 Van Ness Way, Suite 602 . Torrance, CA 90501, USA . Tel: (310) 782-1076 . Fax: (310) 782-1086 . E-mail: antennas@antcom.com . <http://www.antcom.com>

NOTICE OF PROPRIETARY RIGHTS
 THIS DOCUMENT CONTAINS CONFIDENTIAL, TECHNICAL DATA INCLUDING TRADE SECRETS PROPRIETARY TO ANTCOM CORP. DISCLOSURE OF THIS DATA TO ANY OTHER PARTY IS EXPRESSLY PROHIBITED. YOUR USE OF THIS DATA IS LIMITED TO USE WITHIN YOUR COMPANY ONLY AND DOES NOT INCLUDE REPRODUCTION OR FORWARDING. ANY OTHER USE IS EXPRESSLY PROHIBITED WITHOUT PRIOR WRITTEN CONSENT OF ANTCOM CORP.

TNC FEMALE CONNECTOR
 (Option: SMA, QMA, SMB, N)
 (Connector Location can be Customized)

4X 1/4-20 UNC STUD
 (-DT OPTION)

MOUNTING
 20X ø.156 [ø3.96] THRU
 (Bottom or Side Mounting Holes
 can be Customized)

SPECIFICATIONS

REVISIONS	
ZONE	DESCRIPTION

ELECTRICAL:

FREQUENCY: (X.XX - X.XX) GHz - See Below Table for P/N
 PATTERN: DIRECTIONAL
 POLARIZATION: RHCP, LHCP, or LINEAR - See Below Table for P/N
 ANTENNA GAIN: 17 dB
 BEAM WIDTH: EL: 22 Deg.
 AZ: 22 Deg.
 VSWR: 2.0:1
 OUTPUT IMPEDANCE: 50 ohms
 POWER HANDLING: 100 watts
 DC GROUNDING: YES

LNA OPTION (For Rx Only):

LNA GAIN: 33 dB (P1dBout = +13 dBm)
 LNA NOISE FIGURE: 2.2 dB
 LNA VOLTAGE: (+2.5 to +24) Volts DC
 LNA DRAWING CURRENT: < 30 mA

MECHANICAL:

SIZE: 18.8 in x 18.8 in x 0.56 in
 WEIGHT: 2.7 lbs (1.22 Kg)
 FINISH: SKYDROL RESISTANT POLYURETHANE ENAMEL, AND BLACK ANODIZED
 MATERIAL: 6061-T6 ALUMINUM ALLOY BASE COMPOSITE RADOME, IMPACT, ABRASION, UV, SOLVENT, AND SKYDROL RESISTANCE, FIRE RETARDANT
 CONNECTOR: TNC FEMALE (OPTION: SMA, QMA, SMB, N)

ENVIRONMENTAL:

TEMPERATURE: -67 °F TO +185 °F [-55 °C TO +85 °C]
 ALTITUDE: 30,000 ft.
 VIBRATION: > 20 G's
 LEAKAGE: HERMETICALLY SEALED

FEDERAL & MILITARY SPECIFICATIONS:

DESIGN TO: FAA TSO-C144, DO-160D, D0-228, MIL-C-5541, MIL-E-5400, MIL-I-45208A, MIL-STD-810, AND SAE J1455

QUANTITY	DESCRIPTION	PART NO	FINISH	REV
1				3
1				2
1				1

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES FRACTIONS TO DECIMALS ANGLES ± 1/64 .002 .010 ± .1°	ORIGINAL DESIGNED	DATE
	S. HUYNH	Mar-12-12
	S. HUYNH	Mar-12-12
	S. HUYNH	Mar-10-14
	F. TRAN	Mar-10-14
	S. HUYNH	Mar-10-14

ANTCOM CORP. TORRANCE, CALIFORNIA

Rx/Tx- Thuraya or Inmarsat/Iridium Antenna

SCALE 1/1 SHEET 1 OF 1

FREQUENCY BAND:	S/C-BAND POL.	LNA:	CONNECTOR:	COLOR:
T: Rx/Tx Thuraya	V: VERTICAL	A: ACTIVE	S: SMA	-1: GLOSS WHITE #17925 PER FED-STD-595B
IN: Rx/Tx Inmarsat/Iridium	R: RHCP	P: PASSIVE	Q: QMA	-2: LUSTERLESS GRAY #36320 PER FED-STD-595B
1.6-1.9: (1.6 - 1.9) GHz	L: LHVP		SMB: SMB	-3: OLIVE DRAB GREEN #34031 PER FED-STD-595B
2.2-2.3: (2.2 - 2.3) GHz			T: TNC	-4: LUSTERLESS BLACK #37038 PER FED-STD-595B
2.2-2.4: (2.2 - 2.4) GHz			N: N	-5: TAN #33446 PER FED-STD-595B
2.4-2.5: (2.4 - 2.5) GHz				
2.2-2.5: (2.2 - 2.5) GHz				
LS: (1.625 - 1.85)/(2.2 - 2.4) GHz				
X.X-Y.Y: (X.XX - Y.YY) GHz				

18X18A-X.X-Y.YV-P-XT-5

NMO Connector Option is Now Available for Some Antennas