




L1/L2 GPS/L-Band (1-2 GHz) Helix Antenna, P/N: 18x2.5H1215R-P-XN-1-J

500 watts, Low side/Back Lobes for Jamming Applications

2.5" Diameter x 18" Tall, Back Mount Configuration, with N, SMA, TNC, or BNC Connector Options



ISO 9001:2008/FAA Approved Facility

Antenna Mounts: <http://www.antcom.com/documents/catalogs/PeripheralAntennaProducts2.pdf>

ANTCOM CORPORATION . 367 Van Ness Way, #602 . Torrance, CA 90501 . Tel: (310) 782-1076 . Fax: (310) 782-1086 . E-mail: antennas@antcom.com . <http://www.antcom.com>

NOTICE OF PROPRIETARY RIGHTS
THIS DOCUMENT CONTAINS CONFIDENTIAL TECHNICAL DATA INCLUDING TRADE SECRETS PROPRIETARY TO ANTCOM CORP. DISCLOSURE OF THIS DATA TO YOU IS EXPRESSLY CONSIDERED YOUR ASSENT THAT ITS USE IS LIMITED TO USE WITHIN YOUR COMPANY ONLY (AND DOES NOT INCLUDE MANUFACTURE OR PRODUCTION USES). ANY OTHER USE IS EXPRESSLY PROHIBITED WITHOUT PRIOR WRITTEN CONSENT OF ANTCOM CORP.

REVISIONS		DATE	APPROVED
ZONE	REV	DESCRIPTION	

SPECIFICATIONS						
ELECTRICAL:						
FREQUENCY (MHz):	L5 GPS E5, E5a, E5b, Galileo L5 IRNSS	L2 GPS B2 Compass	L2 GLONASS E6 Galileo B3 Compass	Omnistar / L-Band L6 Galileo B1 Compass	L1 GPS E1, E2 Galileo L1 IRNSS	L1 GLONASS
	1176.45 ± 12.0 MHz 1164.45 - 1219.14 MHz 1176.45 ± 15.0 MHz	1227.80 ± 12.0 MHz 1207.14 ± 10.0 MHz	1262.50 ± 7.5 MHz 1266.75 - 1290.75 MHz 1268.52 ± 10.0 MHz	1542.50 ± 14.0 MHz 1542.50 ± 5.0 MHz 1561.098 ± 10.0 MHz	1575.42 ± 15.0 MHz 1575.42 ± 17.0 MHz 1575.42 ± 12.0 MHz	1609.0 ± 7.0 MHz
GAIN (dBic) in FS	> + 10.5 dBic					
SIDE/BACK LOBES:	< -20 dB					
AXIAL RATIO (dB)	1 to 2					
RADIATION PATTERN:	HEMISPHERICAL					
POLARIZATION:	RHCP					
VSWR:	< 1.7 : 1					
POWER HANDLING	500 watts					

MECHANICAL:

SIZE: TOP DIA = 2.50 in [63.50mm], BASE DIA = 3.50 in [88.90mm]
 HEIGHT = 18 in. [457 mm]

WEIGHT: 33.5oz. (950 g)

FINISH: SKYDROL RESISTANT POLYURETHANE ENAMEL
 BASE IRIDITE PER MIL-C-5541F TYPE II CLASS 1A

COLOR: GLOSS WHITE #17925 PER FED-STD-595B
 LUSTERLESS GRAY #36320 PER FED-STD-595B
 OLIVE DRAB GREEN #34031 PER FED-STD-595B
 LUSTERLESS BLACK #37038 PER FED-STD-595B

MATERIAL: 6061-T6 ALUMINUM ALLOY BASE
 COMPOSITE RADOME, IMPACT, ABRASION, UV, SOLVENT,
 AND SKYDROL RESISTANCE, FIRE RETARDANT

CONNECTOR: N-Female
 (OPTION: TNC, SMA, N-Bulkhead, BNC)

ENVIRONMENTAL:

TEMPERATURE: -67 °F TO +185 °F [-55 °C TO +85 °C]
 ALTITUDE: 70,000ft.
 VIBRATION: > 30 G's

LEAKAGE: HERMETICALLY SEALED

FEDERAL & MILITARY SPECIFICATIONS

DESIGN TO: FAA TSO-C144, DO-160D, D0-228, MIL-C-5541F,
 MIL-E-5400, MIL-I-45208A, MIL-STD-810, AND SAE J1455

QUANTITY REQD	DESCRIPTION	PART NO	ITEM NO
8	MOUNTING SCREW: (10-32 Pan Head Phillips, 1/4")	MS51958-59	5
1	Pipe Mount (Item 482m, without Thread insert)	MTR-2-mod	4
1			3
1			2
1			1

HIGH (in):	POLARIZATION:	LNA:	CABLE LENGTH	CONNECTOR	COLOR
	LL: TX: LHCP, RX: LHCP	A1: WITH +34 dB LNA	X: NO CABLE	S: SMA, P: PINS	-1: GLOSS WHITE #17925 PER FED-STD-595B
	LR: TX: LHCP, RX: RHCP	P: WITHOUT LNA	M: WITH MAG MOUNT	M: MMCX, MM: MMCX	-2: LUSTERLESS GRAY #36320 PER FED-STD-595B
	RL: TX: RHCP, RX: LHCP		#: CABLE LENGTH (IN)	N: N, NB: N-Bulkhead	-3: OLIVE DRAB GREEN #34031 PER FED-STD-595B
	RR: TX: RHCP, RX: RHCP		R: RIGHT ANGLE CON.	T: TNC; TB: TNC- Bulkhead	-4: LUSTERLESS BLACK #37038 PER FED-STD-595B
	R: RHCP				
	L: LHCP				

P/N: 18x2.5H1215R-P-XN-1-J

<p>UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES FRACTIONS DECIMALS ANGLES ± 1/64 .005 .015 ± 1° .002 ± .005</p> <p>TOLERANCE 51M PER ANSI Y14.5</p> <p>REVIEW ALL DIMENSIONS BEFORE EXTERNAL EDGES .006 TO .016 HOLE TO HOLE .004 SCREW THREADS PER MIL-S-8879 51'S ON A COORDINATE .25 ± .006 MACHINED SURFACES</p> <p>DO NOT SCALE DRAWING</p>	<p style="text-align: center;">ANTCOM CORP. TORRANCE, CALIFORNIA</p> <p style="text-align: center;">HIGH GAIN IRIDIUM/GPS/GLONASS/ INMARSAT HELIX ANTENNA</p> <p>DESIGNED BY: S. HUYNH DEC-07-09</p> <p>SCALE 1/1</p> <p>SHEET 1 OF 1</p>
--	---