



FAA Approved Facility

L/S/C-Band Antenna

P/N: 2.7GR1.7-2.5V-P-MNB-5 (1.7-2.5GHz L/S-Band, BNC, Tan)

P/N: 2.7GR4.4-5.9V-P-MNB-5 (4.4-5.9GHz C-Band, BNC, Tan)

P/N: 2.7GR1.7-5.9V-P-MNB-5 (1.7-5.9GHz L/S/C-Band, BNC, Tan)

Other Frequency Bands, LNA, Connectors, Colors, and No-Magnet Options Are Also Available

Antenna Mounts/Adapters: <http://www.antcom.com/documents/catalogs/PeripheralAntennaProducts2.pdf>



ANTCOM CORPORATION . 367 Van Ness Way, Suite 602 . Torrance, CA 90501 . Tel: (310) 782-1076 . Fax: (310) 782-1086 . E-mail: [antennas@antcom.com](mailto:antennas@antcom.com) . <http://www.antcom.com>

**NOTICE OF PROPRIETARY RIGHTS**  
THIS DOCUMENT CONTAINS CONFIDENTIAL TECHNICAL DATA INCLUDING TRADE SECRETS PROPRIETARY TO ANTCOM CORP. DISCLOSURE OF THIS DATA TO YOU IS EXPRESSLY CONDITIONED UPON YOUR AGREEMENT THAT ITS USE IS LIMITED TO USE WITHIN YOUR COMPANY ONLY (AND DOES NOT INCLUDE REPRODUCTION OR PROCEEDING THEREON). ANY OTHER USE IS EXPRESSLY PROHIBITED WITHOUT PRIOR WRITTEN CONSENT OF ANTCOM CORP.

**SPECIFICATIONS**

**ELECTRICAL:**

	L/S-BAND	C-BAND	L/S/C-BAND
FREQUENCY:	(1.7 - 2.5 GHz)	(4.4 - 5.9 GHz)	(1.7 - 5.9 GHz)
PATTERN:	OMNIDIRECTIONAL		
POLARIZATION:	VERTICAL		
ANTENNA GAIN :	3 dB		
VSWR:	2:0:1		
OUTPUT IMPEDANCE:	50 Ω		
POWER HANDLING:	>50 watts (without LNA)		
LNA OPTION:	GAIN: 12 dB, NF: 3 dB, OP1dB: +18dB, OIP3: +33dB DC: 12 Volt @ <70mA		

**MECHANICAL:**

SIZE: DIAMETER 2.71 in. [68.81 mm]  
HEIGHT 2.40 in. [60.87 mm]

WEIGHT: <4.94 oz. (140 g)

FINISH: SKYDROL RESISTANT POLYURETHANE ENAMEL  
BASE IRIDITE PER MIL-C-5441F

COLOR: LUSTERLESS GRAY #36320 PER FED-STD-595B  
GLOSS WHITE #17925 PER FED-STD-595B  
OLIVE DRAB GREEN #34031 PER FED-STD-595B  
LUSTERLESS BLACK #37038 PER FED-STD-595B

MATERIAL: 6061-T6 ALUMINUM ALLOY BASE  
THERMOSET PLASTIC RADOME, UV, ABRASION AND SKYDROL RESISTANCE

CONNECTOR: BNC FEMALE  
(OPTION: SMA, QMA, SMB, SMP, BNC, TNC)

**ENVIRONMENTAL:**

TEMPERATURE: -67°F TO +185°F [-55°C TO +85°C]

ALTITUDE: 70,000 ft.

VIBRATION: 10 G's

LEAKAGE: HERMETICALLY SEAL

**FEDERAL & MILITARY SPECIFICATIONS:**

**DESIGN TO:** DO-160D, MIL-C-5541, MIL-E-5400, MIL-I-45208A, AND MIL-STD-810

REVISIONS				
ZONE	REV	DESCRIPTION	DATE	APPROVED

**P/N: 2.7GR1.7-2.5V-P-MNB-5**

FREQUENCY:	LNA:	FEMALE CONNECTOR:	COLOR:
1.7 - 2.5 GHz	A: WITH 12dB LNA	S: SMA; Q/QMA	-1: GLOSS WHITE #17925 PER FED-STD-595B
4.4 - 5.9 GHz	A2: WITH 20dB LNA	SMB; SMP	-2: LUSTERLESS GRAY #36320 PER FED-STD-595B
1.7 - 5.9 GHz	P: WITHOUT LNA	T: TNC; B: BNC	-3: OLIVE DRAB GREEN #34031 PER FED-STD-595B
XX - YY GHz			-4: LUSTERLESS BLACK #37038 PER FED-STD-595B
			-5: DESERT TAN #33446 PER FED-STD-595B

1	2	3	4	5	6	7
1	MAGNET COVER	Magnet-Cover-3i (Item 541g3i)				2
-1	DESCRIPTION	PART NO	MATERIAL	FINISH	TRU NO	

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES		PARTS LIST	
FRACTIONS	DECIMALS	ORIGINAL DRAWN	ORIGINAL DESIGNED
± 1/64	± .005	S. HUYNH May-17-01	S. HUYNH May-17-01
		UPDATED	APPROVED
		S. HUYNH Mar-14-13	S. HUYNH Mar-14-13
		P. TRAN Mar-14-13	
		S. HUYNH Mar-14-13	

**ANTCOM CORP.** TORRANCE, CALIFORNIA

**2.7GR Omnidirectional Vertically Polarized Antenna**

DATE: D 3CVE1 DRAWING NO: 2.7GR1.7-2.5V-P-MNB-5 REV: A

SCALE: 1/1 SHEET 1 OF 1

1. DIMENSIONS IN BRACKETS ARE IN MILLIMETERS [mm]

NOTES: UNLESS OTHERWISE SPECIFIED: