



FAA Approved Facility

(2.20 ± .015) GHz S-Band Telemetry (TM) Antenna, P/N: 2CG22P-R-XS-X-5.75R-871C

For High Speed Vehicle

2.00in. Dia., 5.75in Conformal Radius with Flange Configuration, 871 °C

2 of This Antenna (Top/Bottom) Can be Used with 2-Way Power Divider (P/N: 2G1215S-XS2-2) for Wrap Around Coverage

Other Conformal Radius, Frequencies, Connector, Color, Cable Length and Mounting Options are Available

Antenna Mounts/Adapters: <http://www.antcom.com/documents/catalogs/PeripheralAntennaProducts2.pdf>



ANTCOM CORPORATION . 367 Van Ness Way, Suite 602 . Torrance, CA 90501 . Tel: (310) 782-1076 . Fax: (310) 782-1086 . E-mail: antennas@antcom.com . <http://www.antcom.com>

NOTICE OF PROPRIETARY RIGHTS
THIS DOCUMENT CONTAINS CONFIDENTIAL TECHNICAL DATA INCLUDING TRADE SECRETS PROPRIETARY TO ANTCOM CORP. DISCLOSURE OF THE DATA TO YOU IS EXPRESSLY CONTINGENT UPON YOUR AGREEMENT THAT THE USE IS LIMITED TO USE WITH YOUR COMPANY ONLY. IT DOES NOT INCLUDE MANUFACTURE OR PROCESSING USED, ANY OTHER USE IS EXPRESSLY PROHIBITED WITHOUT PRIOR WRITTEN CONSENT OF ANTCOM CORP.

SPECIFICATIONS		REVISIONS		
ZONE	REV	DESCRIPTION	DATE	APPROVED

ELECTRICAL:

FREQUENCY:	S-BAND (2.200 ± .015) GHz		
RADIATION PATTERN:	HEMISPHERICAL (360° in Azimuth/ >120° in El)		
POLARIZATION:	RHCP		
VSWR:	2:1		
IMPEDANCE:	50 ohms		
ANTENNA GAIN (dBic):	Free Space	3 in G.P.	
@ 90 ° (ZENITH):	+ 1.8	+ 3.8	
@ 10 ° Elevation:	- 5.3	- 4.3	
@ 20 ° Elevation:	- 3.2	- 2.2	
@ 30 ° Elevation:	- 1.5	- 0.7	
@ 60 - 90 ° Elevation:	> 0.5	> 2.5	
BEAM WIDTH (3dB):	100 Deg.	120 Deg.	
AXIAL RATIO:	2.5 dB		
LIGHTNING PROTECTION:	Yes		
RF CENTER PIN DC BLOCK	Yes		
L1 GPS (1575MHz) REJECTION:	30 dB		
POWER HANDLING:	100 Watt		

MECHANICAL:

SIZE: 2.00 in [50.80 mm] DIAMETER
HEIGHT = 0.473in. [12.01 mm]

WEIGHT: 3.4 oz. (96 g)

FINISH: SKYDROL RESISTANT POLYURETHANE ENAMEL
BASE IRIDITE PER MIL-C-5441F
COATING PER MIL-PRF-85582E AND MIL-PRF-85285E

MATERIAL: 316H STAINLESS STEEL HOUSING
CERAMIC RADOME, ABRASION, UV, SOLVENT, SKYDROL RESISTANCE AND FIRE RETARDANT

CONNECTOR: SMA FEMALE
(OPTION: TNC, TNC Bulkhead, N, N Bulkhead, MCX, or MMCX)

ENVIRONMENTAL:

TEMPERATURE: -70 °F TO +1600 °F [-57 °C TO +871 °C]
ALTITUDE: 100,000 ft.
SHOCK/VIBRATION: 100 G's
LEAKAGE: HERMETICALLY SEAL

FEDERAL & MILITARY SPECIFICATIONS:

DESIGN TO: FAA TSO-C144, DO-160D (ENV/EMI), DO-228 (ENV/EMI), MIL-C-5541F, MIL-PRF-39012 (CONN), MIL-STD-810G (ENV/EMI), MIL-HDBK-5400 (ELEC) MIL-STD-464C (ELEC MAG), MIL-STD-130N-1 (ID), MIL-STD-889B (METAL) RCC-319-14 (TERMINATION), RCC-324-01(SAFETY), MIL-STD-1472 MIL-E-5400, MIL-I-45208A, SAE J1455, AND NAS411-1 (HAZ)

ACCEPTANCE TEST PROCEDURE: ATP-GPS-L1L2-100

Top View Dimensions: Diameter 2.000 [50.80], 1.203 [30.56] x 1.203 [30.56]

Side View Dimensions: R5.810 [R147.57], R5.750 [R146.05], .05 X 45° CF, .120 [3.05], .367 [9.32], .413 [10.49], .473 [12.01]

Bottom View Dimensions: 4X 4-40 UNC .12 DEEP ON .601 RAD, Ø1.402 [35.62], .849 [21.58], .295 [7.50]

FREQ. BAND:	LNA:	POLARIZATION:	CONFORMAL RADIUS:
1215: L1/L2	A2: WITH 20 dB LNA	R: RHCP	5.75; 5.75in
15: L1 ONLY	A4: WITH 40 dB LNA	L: LHCP	
22: (2.20 ± .015) GHz	P: WITHOUT LNA	V: VERTICAL	

QUANTITY REQD	DESCRIPTION	PART NO	SPECIFICATION	MATERIAL	FINISH	UNL NO
1	ADHESIVE GASKET	123450-3M-1.20	-	-	-	2
-2	-1					

P/N: 2CG22P-R-XS-X-5.75R-871C

SIZE:	CONNECTOR:	COLOR:
1: 2" SQ.	S: SMA; P: PINS	-1: GLOSS WHITE #17925 PER FED-STD-595B
1.9: 1.9" SQ.	M: MCX; MM: MMCX	-2: LUSTERLESS GRAY #36320 PER FED-STD-595B
2: 2.6" DIA.	SMP: SMP; SSMCR: SSMCR	-3: CAMO GREEN #34094 PER FED-STD-595B
3: 3.5" DIA.	T, TB: TNC, TNC-Bulkhead	-4: LUSTERLESS BLACK #37038 PER FED-STD-595B
		-5: DESERT TAN #33446 PER FED-STD-595B

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES	FRACIONS	TOLERANCES	ANGLES
	DECIMALS	± .015	± 1°
	± 1/64	± .004, .005	

TOLERANCE 5VM PER ANSI Y14.5	BREAK EXTEND EDGES .005 TO .010	FILLET R .005 TO R .010	DRYS ON A COATING PER MIL-STD-883B SURFACES 125	DO NOT SCALE DRAWING

NOTES: UNLESS OTHERWISE SPECIFIED:

ANTCOM CORP. TORRANCE, CALIFORNIA

S-Band Telemetry Antenna

D 3CVE1 | 2CG22P-R-XS-X-5.75R-871C | SHEET 1 OF 1

DATE: 4/3/2016

SCALE: 1/1