



ISO 9001:2008/FAA Approved Facility

(1.25-1.35) GHz Antennas, P/N: 2G1.25-1.35RR-P-XTBC-1 (RHCP); P/N: 2G1.25-1.35LL-P-XTBC-1 (LHCP)  
 (1.35-1.45) GHz Antennas, P/N: 2G1.35-1.45RR-P-XTBC-1 (RHCP); P/N: 2G1.35-1.45LL-P-XTBC-1 (LHCP)  
 (2.00-2.30) GHz Antennas, P/N: 2G2.00-2.30RR-P-XTBC-1 (RHCP); P/N: 2G2.00-2.30LL-P-XTBC-1 (LHCP)  
 (2.20-2.40) GHz Antennas, P/N: 2G2.20-2.40RR-P-XTBC-1 (RHCP); P/N: 2G2.20-2.40LL-P-XTBC-1 (LHCP)  
 (2.40-2.50) GHz Antennas, P/N: 2G2.40-2.50RR-P-XTBC-1 (RHCP); P/N: 2G2.40-2.50LL-P-XTBC-1 (LHCP)  
 (2.56-2.69) GHz Antennas, P/N: 2G2.56-2.69RR-P-XSC-2 (RHCP); P/N: 2G2.56-2.69LL-P-XSC-2 (LHCP)  
 (1.75-2.30) GHz Antennas, P/N: 2G1.80-2.25RR-P-XTBC-1 (RHCP); P/N: 2G1.80-2.25LL-P-XTBC-1 (LHCP)

Antenna Mounts/Adapters: <http://www.antcom.com/documents/catalogs/PeripheralAntennaProducts2.pdf>



ANTCOM CORPORATION . 367 Van Ness Way, Suite 602 . Torrance, CA 90501, USA . Tel: (310) 782-1076 . Fax: (310) 782-1086 . E-mail: [antennas@antcom.com](mailto:antennas@antcom.com) . <http://www.antcom.com>

**SPECIFICATIONS**

**ELECTRICAL:**

RADIATION PATTERN:	HEMISPHERICAL	
POLARIZATION:	RHCP or RHCP	
VSWR:	< 1.5:1	
GAIN (dB):	4 ft G.P.	Free Space
@ 90° (Zenith):	+4.6	+6.1
@ 10° Elevation (Ave):	-1.1	-2.4
@ 20° Elevation (Ave):	+2.2	-0.3
@ 30° Elevation (Ave):	+2.2	+1.0
@ 45° Elevation (Ave):	+3.4	+2.9
@ 70° Elevation (Ave):	+4.4	+5.3
Beam Width (3dB):	110 °	88 °
AXIAL RATIO @ Zenith:	2.0 dB	
IMPEDANCE:	50 Ohms	
POWER HANDLING:	200 Watt	
DC GROUNDING:	YES (LIGHTNING PROTECTION)	

**MECHANICAL:**

SIZE: DIAMETER = 2.63 in.[66.80 mm]  
 HEIGHT = 0.722 in. [18.34 mm]

WEIGHT: 5.15 oz. (146 Kg)

FINISH: SKYDROL RESISTANT POLYURETHANE ENAMEL  
 BASE IRIDITE PER MIL-C-5441F

COLOR: GLOSS WHITE #17925 PER FED-STD-595B  
 LUSTERLESS GRAY #36320 PER FED-STD-595B  
 OLIVE DRAB GREEN #34031 PER FED-STD-595B  
 LUSTERLESS BLACK #37038 PER FED-STD-595B

MATERIAL: 6061-T6 ALUMINUM ALLOY BASE  
 COMPOSITE RADOME, IMPACT, ABRASION, UV, SOLVENT,  
 AND SKYDROL RESISTANCE, FIRE RETARDANT

CONNECTOR: TNC-FEMALE BULKHEAD  
 (OPTION: SMA, TNC, N, N Bulkhead, MCX, MMCX, or Cable)

**ENVIRONMENTAL:**

TEMPERATURE: -67 °F TO +185 °F [-55 °C TO +85 °C]

ALTITUDE: 70,000 ft.

VIBRATION: > 30 G's

LEAKAGE: HERMETICALLY SEAL

**FEDERAL & MILITARY SPECIFICATIONS:**

DESIGN TO: FAA TSO-C144, DO-160D, D0-228, MIL-C-5541,  
 MIL-E-5400, MIL-I-45208A, MIL-STD-810, AND SAE J1455

**REVISIONS**

ZONE	REV	DESCRIPTION	DATE	APPROVED

SIZE:	(START - END) FREQ:	POLARIZATION:	LNA:	FILTER:
1: 2" SQ.	1.25 - 1.35 GHz	LL: LHCP	A1: WITH +23 dB LNA	
1.8: 1.9" SQ.	1.35 - 1.45 GHz	RR: RHCP	A2: WITH +43 dB LNA	
2: 2.6" DIA.	2.00 - 2.30 GHz		P: WITHOUT LNA	
3: 3.5" DIA.	2.20 - 2.40 GHz			
4: MINI ARINC	2.40 - 2.50 GHz			
	X.XX - Y.YY GHz			

P/N: 2GX.XX-Y.YYRR-P-XTBC-1

CABLE LENGTH:	CONNECTOR:	COLOR:
X: NO CABLE	S: SMA; P: PINS	-1: GLOSS WHITE #17925 PER FED-STD-595B
M: WITH MAG. MOUNT	M: MCX; MM: MMCX	-2: LUSTERLESS GRAY #36320 PER FED-STD-595B
#: CABLE LENGTH (IN)	N, NB: N, N-Bulkhead	-3: OLIVE DRAB GREEN #34031 PER FED-STD-595B
R: RIGHT ANGLE CON.	T, TB: TNC, TNC- Bulkhead	-4: LUSTERLESS BLACK #37038 PER FED-STD-595B
		-5: TAN #33446 PER FED-STD-595B

4	MOUNTING SCREWS: 4-40, 3/4"	MS24693-C	-	-	3
4	MOUNTING SCREWS: 6-32, 3/4"	MS24693-C	-	-	2
1	O-RING	MS28775-024	-	-	1

QUANTITY REQD	DESCRIPTION	PART NO	MATERIAL	FINISH	ITEM NO

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES		<b>ANTCOM CORP.</b> TORRANCE, CALIFORNIA
FRACTIONS TO DECIMALS	ANGLES	
± 1/64	± .010	
	± .005	
TOLERANCE SURF PER ANSI Y14.5		
REMOVE ALL BURRS		
BREAK EXTERNAL EDGES .005 TO .015		
SMOOTH TO .005 TO .015		
SMOOTH TO .005 TO .015		
MACHINED SURFACES 12.5		
DO NOT SCALE DRAWING		

ORIGINALLY DRAWN	S. HUYNH	SEP-15-03
ORIGINALLY DESIGNED	S. HUYNH	SEP-15-03
UPDATED	S. HUYNH	FEB-01-13
UPDATE DRAWN	P. TRAN	FEB-01-13
APPROVED	S. HUYNH	FEB-01-13

DR	3CVE1	DRWG NO	2GX.XX-Y.YYRR-P-XTBC-1	REV	
SCALE 1/1		SHEET 1 OF 1			

NMO Connector Option is Now Available for Some Antennas