



FAA Approved Facility

(1.25-1.35) GHz	Antennas,	P/N: 2G1.25-1.35RR-P-XTBC-1 (RHCP);	P/N: 2G1.25-1.35LL-P-XTBC-1 (LHCP)
(1.35-1.45) GHz	Antennas,	P/N: 2G1.35-1.45RR-P-XTBC-1 (RHCP);	P/N: 2G1.35-1.45LL-P-XTBC-1 (LHCP)
(1.70-1.90) GHz	Antennas,	P/N: 2G1.70-1.90RR-P-XTBC-1 (RHCP);	P/N: 2G1.70-1.90LL-P-XTBC-1 (LHCP)
(1.70-2.70) GHz	Antennas,	P/N: 2G1.70-2.70RR-P-XTBC-1 (RHCP);	P/N: 2G1.70-2.70LL-P-XTBC-1 (LHCP)
(1.90-2.20) GHz	Antennas,	P/N: 2G1.90-2.20RR-P-XTBC-1 (RHCP);	P/N: 2G1.90-2.20LL-P-XTBC-1 (LHCP)
(2.00-2.30) GHz	Antennas,	P/N: 2G2.00-2.30RR-P-XTBC-1 (RHCP);	P/N: 2G2.00-2.30LL-P-XTBC-1 (LHCP)
(2.20-2.40) GHz	Antennas,	P/N: 2G2.20-2.40RR-P-XTBC-1 (RHCP);	P/N: 2G2.20-2.40LL-P-XTBC-1 (LHCP)
(2.40-2.50) GHz	Antennas,	P/N: 2G2.40-2.50RR-P-XTBC-1 (RHCP);	P/N: 2G2.40-2.50LL-P-XTBC-1 (LHCP)
(2.56-2.69) GHz	Antennas,	P/N: 2G2.56-2.69RR-P-XSC-2 (RHCP);	P/N: 2G2.56-2.69LL-P-XSC-2 (LHCP)
(4.00-6.00) GHz	Antennas,	P/N: 2G4.00-6.00RR-P-XSC-2 (RHCP);	P/N: 2G4.00-6.00LL-P-XSC-2 (LHCP)

GMM 1800  
UMTS 2100



ANTCOM CORPORATION . 367 Van Ness Way, Suite 602 . Torrance, CA 90501 . Tel: (310) 782-1076 . Fax: (310) 782-1086 . E-mail: antennas@antcom.com . http://www.antcom.com

**NOTICE OF PROPRIETARY RIGHTS**

THIS DOCUMENT CONTAINS CONFIDENTIAL, TECHNICAL DATA BELONGING TO ANTCOM CORPORATION. ANY DISCLOSURE OF THIS DATA TO ANY OTHER PARTY WITHOUT THE WRITTEN CONSENT OF ANTCOM CORPORATION IS STRICTLY PROHIBITED. ANY OTHER USE IS STRICTLY PROHIBITED WITHOUT PRIOR WRITTEN CONSENT OF ANTCOM CORPORATION.

**SPECIFICATIONS**

**ELECTRICAL:**

RADIATION PATTERN:	HEMISPHERICAL	
POLARIZATION:	RHCP	
VSWR:	< 1.5:1	
GAIN (dB):	4 ft G.P.	Free Space
@ 90° (Zenith):	+4.6	+6.1
@ 10° Elevation (Ave):	-1.1	-2.4
@ 20° Elevation (Ave):	+2.2	-0.3
@ 30° Elevation (Ave):	+2.2	+1.0
@ 45° Elevation (Ave):	+3.4	+2.9
@ 70° Elevation (Ave):	+4.4	+5.3
Beam Width (3dB):	110 °	88 °
AXIAL RATIO @ Zenith:	2.0 dB	
IMPEDANCE:	50 Ohms	
POWER HANDLING:	200 Watt	
DC GROUNDING:	YES (LIGHTNING PROTECTION)	

**MECHANICAL:**

SIZE: DIAMETER = 2.63 in. [66.80 mm]  
HEIGHT = 0.988 in. [25.10 mm]

WEIGHT: 5.15 oz. (.146 Kg)

FINISH: SKYDROL RESISTANT POLYURETHANE ENAMEL  
BASE IRIDITE PER MIL-C-5441F

COLOR: GLOSS WHITE #17925 PER FED-STD-595B  
LUSTERLESS GRAY #36320 PER FED-STD-595B  
OLIVE DRAB GREEN #34031 PER FED-STD-595B  
LUSTERLESS BLACK #37038 PER FED-STD-595B

MATERIAL: 6061-T6 ALUMINUM ALLOY BASE  
COMPOSITE RADOME, IMPACT, ABRASION, UV, SOLVENT,  
AND SKYDROL RESISTANCE, FIRE RETARDANT

CONNECTOR: TNC-FEMALE BULKHEAD  
(OPTION: SMA, TNC, N, N Bulkhead, MCX, MMCX, or Cable)

**ENVIRONMENTAL:**

TEMPERATURE: -67 °F TO +185 °F [-55 °C TO +85 °C]

ALTITUDE: 70,000 ft.

VIBRATION: > 30 G's

LEAKAGE: HERMETICALLY SEAL

**FEDERAL & MILITARY SPECIFICATIONS:**

**DESIGN TO:** FAA TSO-C144, DO-160D, D0-228, MIL-C-5541,  
MIL-E-5400, MIL-I-45208A, MIL-STD-810, AND SAE J1455

2. MOUNTING SCREWS ARE SUPPLIED BY ANTCOM CORPORATION

1. DIMENSIONS IN BRACKETS ARE IN MILLIMETERS [mm]

NOTES: UNLESS OTHERWISE SPECIFIED:

SIZE:	(START - END) FREQ.	POLARIZATION:	LNA:	FILTER:
1: 2" SQ.	1.25 - 1.35 GHz	L/LHCP	A1: WITH +23 dB LNA	
1.8" 1.9" SQ.	1.35 - 1.45 GHz	RR/RHCP	A2: WITH +43 dB LNA	
2: 2.6" DIA.	2.00 - 2.30 GHz		P: WITHOUT LNA	
3: 3.5" DIA.	2.20 - 2.40 GHz			
4: MINI ARINC	2.40 - 2.50 GHz			
	X.XX - Y.YY GHz			

**P/N: 2GX.XX-Y.YYRR-P-XTBC-1**

CABLE LENGTH:	CONNECTOR:	COLOR:
X: NO CABLE	S: SMA; P: RINS	+1: GLOSS WHITE #17925 PER FED-STD-595B
M: WITH MAG. MOUNT	M: MCX; MM: MMCX	+2: LUSTERLESS GRAY #36320 PER FED-STD-595B
#: CABLE LENGTH (IN)	N, NB, N, N-Bulkhead	+3: OLIVE DRAB GREEN #34031 PER FED-STD-595B
R: RIGHT ANGLE CON.	T, TB: TNC, TNC-Bulkhead	+4: LUSTERLESS BLACK #37038 PER FED-STD-595B
		+5: TAN #33446 PER FED-STD-595B

2. MOUNTING SCREWS ARE SUPPLIED BY ANTCOM CORPORATION

1. DIMENSIONS IN BRACKETS ARE IN MILLIMETERS [mm]

NOTES: UNLESS OTHERWISE SPECIFIED:

QUANTITY	REVISION	DESCRIPTION	PART NO	MATERIAL	FINISH	REV
4	1	MOUNTING SCREWS: 4-40, 3/4"	MS24693-C	-	-	3
4	2	MOUNTING SCREWS: 6-32, 3/4"	MS24693-C	-	-	2
1	1	O-RING	MS28775-024	-	-	1

**ANTCOM CORP.** TORRANCE, CALIFORNIA

**2.6" Dia. FLAT FIXED MOUNT**

**L/S/WIFI ANTENNA**

SCALE 1/1

SHEET 1 OF 1

NMO Connector Option is Now Available for Some Antennas