



ISO 9001:2008/FAA Approved

(0.81-0.96) GHz	Antennas,	P/N: 2G0.81-0.96RR-P-XTBC-1 (RHCP);	P/N: 2G 0.81-0.96 LL-P-XTBC-1 (LHCP)	GSM 800
(1.25-1.35) GHz	Antennas,	P/N: 2G1.25-1.35RR-P-XTBC-1 (RHCP);	P/N: 2G1.25-1.35LL-P-XTBC-1 (LHCP)	GMM 1800
(1.35-1.45) GHz	Antennas,	P/N: 2G1.35-1.45RR-P-XTBC-1 (RHCP);	P/N: 2G1.35-1.45LL-P-XTBC-1 (LHCP)	UMTS 2100
(1.70-1.90) GHz	Antennas,	P/N: 2G1.70-1.90RR-P-XTBC-1 (RHCP);	P/N: 2G1.70-1.90LL-P-XTBC-1 (LHCP)	
(1.70-2.70) GHz	Antennas,	P/N: 2G1.70-2.70RR-P-XTBC-1 (RHCP);	P/N: 2G1.70-2.70LL-P-XTBC-1 (LHCP)	
(1.90-2.20) GHz	Antennas,	P/N: 2G1.90-2.20RR-P-XTBC-1 (RHCP);	P/N: 2G1.90-2.20LL-P-XTBC-1 (LHCP)	
(2.00-2.30) GHz	Antennas,	P/N: 2G2.00-2.30RR-P-XTBC-1 (RHCP);	P/N: 2G2.00-2.30LL-P-XTBC-1 (LHCP)	
(2.20-2.40) GHz	Antennas,	P/N: 2G2.20-2.40RR-P-XTBC-1 (RHCP);	P/N: 2G2.20-2.40LL-P-XTBC-1 (LHCP)	
(2.40-2.50) GHz	Antennas,	P/N: 2G2.40-2.50RR-P-XTBC-1 (RHCP);	P/N: 2G2.40-2.50LL-P-XTBC-1 (LHCP)	
(2.56-2.69) GHz	Antennas,	P/N: 2G2.56-2.69RR-P-XSC-2 (RHCP);	P/N: 2G2.56-2.69LL-P-XSC-2 (LHCP)	
(4.00-6.00) GHz	Antennas,	P/N: 2G4.00-6.00RR-P-XSC-2 (RHCP);	P/N: 2G4.00-6.00LL-P-XSC-2 (LHCP)	



ANTCOM CORPORATION . 367 Van Ness Way, Suite 602 . Torrance, CA 90501, USA . Tel: (310) 782-1076 . Fax: (310) 782-1086 . E-mail: antennas@antcom.com . http://www.antcom.com

Other Frequencies, Antenna Sizes, Connectors/Locations, and Mounting Configurations are Available

NMO Connector Option is Now Available for Some Antennas

NOTICE OF PROPRIETARY RIGHTS

THIS DOCUMENT CONTAINS CONFIDENTIAL TECHNICAL DATA BELONGING TO ANTCOM CORPORATION. ANY DISCLOSURE OF THIS DATA TO ANY OTHER PARTY WITHOUT THE WRITTEN CONSENT OF ANTCOM CORPORATION IS STRICTLY PROHIBITED WITHOUT PRIOR WRITTEN CONSENT OF ANTCOM CORP.

REVISIONS

ZONE	REV	DESCRIPTION	DATE	APPROVED
A		HEIGHT	10/06/16	S.H

SPECIFICATIONS

7

6

ELECTRICAL:

RADIATION PATTERN:	HEMISPHERICAL	
POLARIZATION:	RHCP	
VSWR:	< 1.5:1	
GAIN (dB):	4 ft G.P.	Free Space
@ 90° (Zenith):	+4.6	+6.1
@ 10° Elevation (Ave):	-1.1	-2.4
@ 20° Elevation (Ave):	+2.2	-0.3
@ 30° Elevation (Ave):	+2.2	+1.0
@ 45° Elevation (Ave):	+3.4	+2.9
@ 70° Elevation (Ave):	+4.4	+5.3
Beam Width (3dB):	110 °	88 °
AXIAL RATIO @ Zenith:	2.0 dB	
IMPEDANCE:	50 Ohms	
POWER HANDLING:	200 Watt	
DC GROUNDING:	YES (LIGHTNING PROTECTION)	

MECHANICAL:

SIZE: DIAMETER = 2.63 in.[66.80 mm]
HEIGHT = 0.886 in. [22.50 mm]

WEIGHT: 5.15 oz. (.146 Kg)

FINISH: SKYDROL RESISTANT POLYURETHANE ENAMEL
BASE IRIDITE PER MIL-C-5441F

COLOR: GLOSS WHITE #17925 PER FED-STD-595B
LUSTERLESS GRAY #36320 PER FED-STD-595B
OLIVE DRAB GREEN #34031 PER FED-STD-595B
LUSTERLESS BLACK #37038 PER FED-STD-595B

MATERIAL: 6061-T6 ALUMINUM ALLOY BASE
COMPOSITE RADOME, IMPACT, ABRASION, UV, SOLVENT,
AND SKYDROL RESISTANCE, FIRE RETARDANT

CONNECTOR: TNC-FEMALE BULKHEAD
(OPTION: SMA, TNC, N, N Bulkhead, MCX, MMCX, or Cable)

ENVIRONMENTAL:

TEMPERATURE: -67 °F TO +185 °F [-55 °C TO +85 °C]

ALTITUDE: 70,000 ft.

VIBRATION: > 30 G's

LEAKAGE: HERMETICALLY SEAL

FEDERAL & MILITARY SPECIFICATIONS:

DESIGN TO: FAA TSO-C144, DO-160D, D0-228, MIL-C-5541,
MIL-E-5400, MIL-I-45208A, MIL-STD-810, AND SAE J1455

MECHANICAL:

SIZE: DIAMETER = 2.63 in.[66.80 mm]
HEIGHT = 0.886 in. [22.50 mm]

WEIGHT: 5.15 oz. (.146 Kg)

FINISH: SKYDROL RESISTANT POLYURETHANE ENAMEL
BASE IRIDITE PER MIL-C-5441F

COLOR: GLOSS WHITE #17925 PER FED-STD-595B
LUSTERLESS GRAY #36320 PER FED-STD-595B
OLIVE DRAB GREEN #34031 PER FED-STD-595B
LUSTERLESS BLACK #37038 PER FED-STD-595B

MATERIAL: 6061-T6 ALUMINUM ALLOY BASE
COMPOSITE RADOME, IMPACT, ABRASION, UV, SOLVENT,
AND SKYDROL RESISTANCE, FIRE RETARDANT

CONNECTOR: TNC-FEMALE BULKHEAD
(OPTION: SMA, TNC, N, N Bulkhead, MCX, MMCX, or Cable)

ENVIRONMENTAL:

TEMPERATURE: -67 °F TO +185 °F [-55 °C TO +85 °C]

ALTITUDE: 70,000 ft.

VIBRATION: > 30 G's

LEAKAGE: HERMETICALLY SEAL

FEDERAL & MILITARY SPECIFICATIONS:

DESIGN TO: FAA TSO-C144, DO-160D, D0-228, MIL-C-5541,
MIL-E-5400, MIL-I-45208A, MIL-STD-810, AND SAE J1455

ENVIRONMENTAL:

TEMPERATURE: -67 °F TO +185 °F [-55 °C TO +85 °C]

ALTITUDE: 70,000 ft.

VIBRATION: > 30 G's

LEAKAGE: HERMETICALLY SEAL

FEDERAL & MILITARY SPECIFICATIONS:

DESIGN TO: FAA TSO-C144, DO-160D, D0-228, MIL-C-5541,
MIL-E-5400, MIL-I-45208A, MIL-STD-810, AND SAE J1455

DESIGN TO: FAA TSO-C144, DO-160D, D0-228, MIL-C-5541,
MIL-E-5400, MIL-I-45208A, MIL-STD-810, AND SAE J1455

SIZE:	(START - END) FREQ:	POLARIZATION:	LNA:	FILTER:
1: 2" SQ.	1.25 - 1.35 GHz	L/LHCP	A1: WITH +23 dB LNA	
1.8" 1.9" SQ.	1.35 - 1.45 GHz	RR/RHCP	A2: WITH +43 dB LNA	
2: 2.6" DIA.	2.00 - 2.30 GHz		P: WITHOUT LNA	
3: 3.5" DIA.	2.20 - 2.40 GHz			
4: MINI ARINC	2.40 - 2.50 GHz			
	X.XX - Y.YY GHz?			

QUANTITY REQD	DESCRIPTION	PART NO	MATERIAL	FINISH	ITEM NO
4	MOUNTING SCREWS: 4-40, 3/4"	MS24693-C	-	-	3
4	MOUNTING SCREWS: 6-32, 3/4"	MS24693-C	-	-	2
1	O-RING	MS28775-024	-	-	1

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES

FRACTIONS: DECIMALS: ANGLES: ± 1/64 .0005 .010 ± 1°

TOLERANCE 5VM PER ANSI Y14.5

REMOVE ALL BURRS

PROTECT EXTERNAL EDGES .005 TO .010

SHEET # 2055 OF 2 SHEETS

DESIGNED BY S. HUYNH

DATE: 08-15-15

APPROVED BY P. TRAN

DATE: 08-16-15

APPROVED BY S. HUYNH

DATE: 08-16-15

DO NOT SCALE DRAWING

ANTCOM CORP. TORRANCE, CALIFORNIA

2.6" Dia. FLAT FIXED MOUNT L/S/WIFI ANTENNA

SCALE: 1/1

SHEET 1 OF 1

NOTES: UNLESS OTHERWISE SPECIFIED:

2. MOUNTING SCREWS ARE SUPPLIED BY ANTCOM CORPORATION

1. DIMENSIONS IN BRACKETS ARE IN MILLIMETERS [mm]

CABLE LENGTH:	CONNECTOR:	COLOR:
X: NO CABLE	S: SMA; P: PINS	-1: GLOSS WHITE #17925 PER FED-STD-595B
M: WITH MAG. MOUNT	M: MCX; MM: MMCX	-2: LUSTERLESS GRAY #36320 PER FED-STD-595B
#: CABLE LENGTH (IN)	N, NB, N, N-Bulkhead	-3: OLIVE DRAB GREEN #34031 PER FED-STD-595B
R: RIGHT ANG. E CONN.	T, TB: TNC, TNC-Bulkhead	-4: LUSTERLESS BLACK #37038 PER FED-STD-595B
		-5: TAN #33446 PER FED-STD-595B